


SL-NTS24CV36W-CA

24V DC Power Supply with 36 Watt



TECHNICAL DRAWING



PRODUCT FEATURES

- » 24 Volt DC power supply unit with 2 meter connection cable
- » Direct connection of up to 4 x 24V DC Led lights or Siro Receiver.
- » 36 watts, maximum output power (max. 3A per connection)
- » Connection of wired sensors (TOUCH, PIR, DOOR) to control the power supply output
- » **Wired sensors must not be used together with connected SIRO receivers (at the power supply unit output)!**
- » Short-circuit protection & overload protection
- » Low stand-by consumption < 0.13 watts

TECHNICAL DATA

- » Input voltage:..... 200 - 240V AC
- » Output voltage: 24V DC
- » Output current: 1.5 A
- » Power: 36 Watt
(10% reserve recommended)
- » Efficiency: 89%
- » Standby P: 0.13 W
- » Idle power P_{no}:..... N/A
- » Networked standby power P_{net}:..... N/A
- » Protection class:..... IP 20
- » Mains frequency input:..... 50 - 60 Hz
- » Housing color: white
- » Ambient temperature:..... -20° - +45°C
- » Protection: Short-circuit &
Overload protection
- » Length:..... 112,00 mm
- » Width:..... 39,10 mm
- » Height:..... 18,00 mm
- » Weight:..... 172 g

